

Mulch Selection Chart

PRODUCT	APPLICATION	SLOPE	MAX. CONTINUOUS SLOPE LENGTH	CONDITIONS	RATE. LBS./ PER ACRE
TERRA-WOOD	GENERAL SEEDING	<2.5:1	35 FT.	MODERATE SITES	2,500
		<3:1			2,000
		<4:1			1,500
HYDRO-STRAW	GENERAL SEEDING	<4:1	35 FT.	MODERATE SITES	2,000
		<3:1			3,000
		<2:1			4,000
TERRA-WOOD W/TACKING AGENT 3	GENERAL SEEDING	<2:1	40 FT.	MODERATE SITES	2,500-3,500
		<2.5:1			2,000
		<3:1			1,500
HYDRO-STRAW GUAR PLUS	GENERAL SEEDING	<4:1	40 FT.	MODERATE SITES	2,000
		<3:1			2,500
		<2:1			3,000
TACKING AGENT 3	3% BY WEIGHT				
HYDRO-BLANKET BFM	<12 MONTH CONTROL	<1:1	70 FT.	SPECIFIC SITES	4,000
		<2:1			3,500
		<3:1			3,000
HYDRO-STRAW BFM	<12 MONTH CONTROL	>2H:1V and <1H:1V	70 FT.	SPECIFIC SITES	4,500
		>3H:1V AND <2H:1V			3,500
		<3H:1V			3,000
TERRA-MATRIX SMM	<6 MONTH CONTROL	>2.5:1 and <2.1:1	50 FT.	CRITICAL SITES	3,500
		>3:1 and <2.5:1			3,000
		>4:1 and <3:1			2,500
		4:1			2,000
FLEXTERRA FGM	12 – 18 MONTH CONTROL	>1:1	70FT.	CRITICAL SITES	4,500
		>2:1 and <1:1			4,000
		>3:1 and <2:1			3,500
		<3:1			3,000
COCOFLEX ET-FGM	18 – 24 MONTH CONTROL	>1:1	100 FT.	CRITICAL SITES	4,500
JET SPRAY POURABLE FIBER MULCH	GENERAL SEEDING	2:1 TO 1:1	35 FT.	MODERATE SITES	3,500
		3:1 TO 2:1			3,000
		3:1			2,500
		MOD TO 4:1			2,000